

ITPC-A156

Intel® Core™/Celeron® Processor - 15.6" Touch Panel PC



FEATURES

- Fanless Aluminum Design
- Support Intel® Core™/Celeron® Processor
- High-definition industrial LCD screen
- Capacitive type multi-touch screen
- Support VESA Mount, Wall Mount ect.


SPECIFICATION

SYSTEM	
Processor	Intel® Celeron® J1900 (quad core four threads, 1.99GHz) Intel® Core™ i5-4300U (dual core quad threads, 1.9GHz, Max. Turbo 2.9GHz)
Chipset	Intel® CPU Integrated Chip
Memory	1 × DDR3L 1333/1600MHz SODIMM, Max. 8 GB
BIOS	64MB Flash ROM
Display Chip	Intel® HD Graphics (Intel® Celeron® J1900) Intel® HD Graphics 4400 (Intel® Core™ i5-4300U)
Display Port	1 × HDMI, 1 × LVDS, 1 × VGA Support synchronous/asynchronous 2 display
Storage	1 × MSATA 1 × 2.5-inch HDD
Expansion	1 × Mini PCIe (support WiFi/Bluetooth/3G/4G optional)
OS Support	Windows 7, Windows 8, Windows 10, Linux
I/O	2 × USB 3.0 2 × USB 2.0 2 × RS232 COM Ports, COM3 support RS232/422/485 (6 × COM Ports optional) 1 × VGA 1 × HDMI 1 × 1000Mbps LAN Ports (2 × LAN Ports optional) 1 × DC-In 1 × 3 Pin Power Connector 1 × Mic 1 × Line Out
Power	DC 12V (DC 9~36V optional)
Speaker	2 × 8Ω2W
DISPLAY	
Display Type	15.6" TFT-LCD
Brightness	250 cd/m ²
Viewing Angle	H (60/60), V (45/45)
Contrast	16:9
Resolution	1366 × 768
Touchscreen Type	Capacitive type multi touch screen (touch life can reach more than 50 million times)
ENVIRONMENT	
Operating Temperature	0°C ~ 40°C (Commercial HDD), -10°C ~ 50°C (Industrial SSD), surface air flow
Relative Humidity	5% ~ 95% (non-condensing)
Certification	CE, CCC, FCC Class A, RoHS
MECHANISM	
Dimension	397 × 246.5 × 44 mm
Embedded Size	386 × 235 mm
Weight	3.25 kg



DIMENSION

unit:mm



ORDER INFORMATION

ITPC-A156	CPU	Specification
Configuration 1	Intel® Celeron® J1900	Standard I/O
Configuration 2	Intel® Core™ i5-4300U	2 × LAN Ports, 6 × COM Ports (optional)
Configuration 3	Intel® Celeron® J1900	Standard I/O
Configuration 4	Intel® Core™ i5-4300U	2 × LAN Ports, 6 × COM Ports (optional)

ACCESSORY

Part Name	Quantity	Specification
Power Adapter	1	12V 5A
Power Cord	1	CN, US, UK, EU etc.
Embedded Buckle	4	Standard
CD Driver	1	Neutral
Desktop, Wall Mount, Standing Bracket	1	Optional